

Resistenza allo scivolamento - Slip resistance - Résistance au glissement - Rutschfestigkeit



DIN 51130

R9

ANSI A137.1 BOT 3000

≥ 0,42

BCRA TORTUS

> 0,40

Sforzo di rottura (S) - Breaking strength (S) - Charge de rupture (S) - Bruchlast (S)



ISO 10545-4

≥ 1000 N

Visibilità delle impronte - Tread mark visibility - Visibilité des empreintes - Sichtbarkeit von Fußspuren



METODO COTTO D'ESTE-COTTO D'ESTE METHOD-MÉTHODE COTTO D'ESTE - COTTO D'ESTE VERFAHREN

A

Facilità di pulizia - Cleaning easiness - Facilité d'élimination de la tache - Reinigungsaufwand



METODO COTTO D'ESTE-COTTO D'ESTE METHOD-MÉTHODE COTTO D'ESTE - COTTO D'ESTE VERFAHREN

1

Resistenza all'attacco chimico - Resistance to chemical etching - Résistance à l'attaque chimique - Beständigkeit gegen Chemikalien



ISO 10545-13

ULA-UHA

Resistenza alle macchie - Stain resistance - Résistance aux taches - Fleckenbeständigkeit



ISO 10545-14

CLASSE 5

Resistenza all'abrasione profonda - Deep abrasion resistance - Résistance à l'abrasion profonde - Widerstand gegen Tiefenabrieb



ISO 10545-6

CONFORME

Assorbimento d'acqua - Water absorption - Absorption d'eau - Wasseraufnahmefähigkeit



ISO 10545-3

≤ 0,1%

Resistenza al gelo - Frost resistance - Résistance au gel - Frostbeständigkeit



ISO 10545-12

Ingelivo - Frost proof

Stonalizzazione - Deshading - Dénuancement - Enttonalisierung



ANSI A137.1

V2



Residenziale
Residential
Résidentiel
Wohnbereich



Pubblico
Public
Public
Öffentlich